

MODELS/SPECS

851

Capacity: 850 bushels¹ | Unloads: 475 bu/min²



DIMENSIONS & SPECIFICATIONS

Weight

| | |
|-----------------------------|-------------|
| Radial Tires (Empty) | 14,640 lbs. |
| Tracks by Camso (Empty) | N/A |
| Hitch (Empty) | 2,500 lbs. |
| Hitch (Loaded) ¹ | 5,000 lbs. |

Width - Overall

| | |
|--------------|--------|
| Radial Tires | 13' 5" |
|--------------|--------|

Height

| | |
|-------------------|--------|
| Short Side Height | 11' 1" |
| High Side Height | 12' 1" |

Length - Overall

| | |
|--------|--------|
| Length | 28' 4" |
|--------|--------|

UltraFlyte™ Auger

| | |
|----------|--------|
| Diameter | 20" |
| Reach | 7' 3" |
| Height | 13' 4" |

Other

| | |
|------------------------|-------------------|
| Hydraulic Requirements | 3 SCVs |
| PTO | 1 3/4" - 1000 rpm |

1051

Capacity: 1050 bushels¹ | Unloads: 475 bu/min²



DIMENSIONS & SPECIFICATIONS

Weight

| | |
|-----------------------------|-------------|
| Radial Tires (Empty) | 15,100 lbs. |
| Tracks by Camso (Empty) | 23,000 lbs. |
| Hitch (Empty) | 2,500 lbs. |
| Hitch (Loaded) ¹ | 5,000 lbs. |

Width - Overall

| | |
|-----------------------|--------|
| Radial Tires & Tracks | 13' 5" |
|-----------------------|--------|

Height

| | |
|-------------------|--------|
| Short Side Height | 11' 7" |
| High Side Height | 12' 7" |

Length - Overall

| | |
|--------|--------|
| Length | 30' 4" |
|--------|--------|

UltraFlyte™ Auger

| | |
|----------|--------|
| Diameter | 20" |
| Reach | 7' 3" |
| Height | 13' 4" |

Other

| | |
|------------------------|-------------------|
| Hydraulic Requirements | 3 SCVs |
| PTO | 1 3/4" - 1000 rpm |

¹ Cart capacity and hitch weight are based on #2 corn at 15% moisture (56 lb. test weight). Cart capacity and hitch weight may vary based on crop type, grade, moisture and other environmental factors. ² Bushels per minute may vary with moisture content of grain and/or PTO rpm.